


COMMERCIAL/INDUSTRIAL


ARTEMIS SERIES



MOUNTING OPTIONS & DIMENSIONS (Weights shown may vary with mounting options)



With Pendant Mount (PD). Weight: 8 lbs



With Ceiling Mount (CL). Weight: 8 lbs

LIGHTING SOLUTIONS THAT OUTSHINE ALL OTHERS.  **ephesus**

▶ 315.579.2873 ▶ EphesusLighting.com

ARTEMIS SERIES

Provide exceptional security lighting for enhanced safety and visibility in both indoor and open-air parking garages. Constructed of heavy-duty aluminum for long-term performance, this rugged, impact-resistant and maintenance-free LED solution is unaffected by fluctuating temperatures, with substantial energy savings of up to 85%.


0-10V dimming is a standard feature in the Artemis Series.

	ARTEMIS 40	ARTEMIS 60
Lumen Output*	3,860	5,571
System Watts	40	60
Efficacy	97	93
Input Voltage	VL:90-277VAC	VL:90-277VAC
Power Factor	>0.95	>0.95
CRI	>70	>70
CCT	5000K	5000K
Operating Temp	-40°C to 55°C	-40°C to 55°C
0-10V Dimming	Standard	Standard
L70 Hours	461,000 hours	340,000 hours
IP Rating	IP66	IP66

ILLUMINATION TABLES ²

ARTEMIS 40 - Average Illumination (FC)						ARTEMIS 60 - Average Illumination (FC)					
Height	Spacing					Height	Spacing				
	15 FT	20 FT	25 FT	30 FT	35 FT		15 FT	20 FT	25 FT	30 FT	35 FT
10 FT	22	13	8	6	4	10 FT	29	17	11	7	6
15 FT	22	12	8	5	4	15 FT	29	16	10	7	6
20 FT	21	12	8	5	4	20 FT	28	16	10	7	6
25 FT	20	11	7	5	4	25 FT	27	15	10	7	5
30 FT	20	11	7	5	4	30 FT	26	15	9	7	5

STANDARD PRODUCTS, OPTIONS AND ORDERING LOGIC

STANDARD PRODUCT								
Model	Product Code	Wattage	CCT	Finish	Voltage	Mounting	Optics	Accessories
Artemis 40	AR	40	C	BLK	VL	PD	5W	N
Artemis 60	AR	60	C	BLK	VL	PD	5W	N
	AR		C				5W	N
Available Options			C (Cool) N (Neutral) W (Warm)	BLK (Black) BNZ (Bronze) WHT (White)	VL VH ³	PD (Pendant Mount) CL (Ceiling Mount)		N (None)

Notes 1 The specifications listed were obtained under optimal testing conditions. Changes in options, features and conditions may result in slightly different performance specifications among fixtures.
 2 Data based on a 300' x 300' room, 80/50/20 reflectance.
 3 VH:277-582VAC



Representante
 Bosque de Duraznos #69 - Torre B 1107-A
 Col. Bosques de las Lomas, México DF. 11700
 Tel: +52 55 5251 2008
 ventas@bhpenergy.mx /
 © 2015 BHP Energy México Todos Los Derechos Reservados